

# > RVS

## Regolatore di velocità ad autotrasformatore monofase 0,5 A

Single-phase self-transformer speed regulator 0,5 A



### DESCRIZIONE

Variatore di tensione manuale mediante autotrasformatore con selettore a 5 posizioni. Assenza di ronzio elettrico nel motore. Adatto a motori asincroni monofase regolabili.

### CONSTRUZIONE

- Alimentazione 230V-1Ph-50/60Hz.
- Corrente nominale max 0.5A.
- Tensione di uscita 1(125V)-2(140V)-3(160V)-4(200V)-5(230V).
- Protezione IP 42.
- Contenitore in tecnopolimero RAL9016 (bianco).
- Peso Kg.0,7

### DESCRIPTION

Manual voltage converter by self-transformer switchover, 5 step options. Minimum magneto-acoustic noise in the motor. Suitable for single-phase asynchronous adjustable motors.

### CONSTRUCTION

- Supply 230V-1Ph-50/60Hz.
- Nominal current max 0.5A.
- Output voltage 1(125V)-2(140V)-3(160V)-4(200V)-5(230V).
- Protection IP 42.
- Housing in techno-polymer RAL9016 (white).
- Weight Kg.0,7.

## DIMENSIONI E SCHEDA DI COLLEGAMENTO Dimensions and wiring diagram

RVS

Dimensioni in mm / Dimensions in mm

